

# Chevron Delo® Bumper-to-Bumper Protection for Construction Equipment

## Hydraulic System

- Delo® TorqForce MP (CAT T0-4M)
- Delo TorqForceTM 10W (CAT T0-4)
- Delo TorqForce Syn 5W-20
- Rando® HDZ
- Ursa Hydraulic Oil 10W

## Transmissions

- Delo TorqForce MP (CAT T0-4M)
- Delo TorqForce 30 (CAT T0-4)
- Delo 400 10W (hydrostatic)
- Delo Syn-Trans HD 50

## Engine Crankcase

- Delo 600 ADF 15W-40
- Delo 400 XSP 5W-40
- Delo 400 XLE 10W-30
- Delo 400 XLE 15W-40
- Delo 400 SDE 15W-40

## Bearings and Grease Points

- Starplex® HD
- Starplex HD M5
- Starplex Syn EP M5
- Starplex HD M3

## Differentials and Gear Drives

- Delo Syn-Gear XDM 75W-90
- Delo Gear ESI 80W-90
- Delo TorqForce 50 (CAT T0-4)
- Delo Syn-Gear HD 75W-90

## Coolant System

- Delo ELC Advanced Antifreeze/Coolant
- Delo ELC Antifreeze/Coolant
- Delo XLC Antifreeze/Coolant

Available as ISOCLEAN® Certified

These product recommendations provide general guidelines. All manufacturers have different coolant and lubricant requirements and recommendations. It will be important to contact a Chevron representative or refer to the Original Equipment Manufacturer manual to confirm the proper product is used for the application. Visit [chevron-gsc.force.com/lubeteksupport](http://chevron-gsc.force.com/lubeteksupport) for confirmation of specific OEM specifications.



A Chevron company product

©2023 Chevron. All rights reserved. All trademarks are property of Chevron Intellectual Property LLC or their respective owners.