

Chevron Delo® Bumper-to-Bumper Protection for Surface Mining Equipment

Hydraulic System

- Delo® TorqForce MP (CAT TO-4M)
- Delo TorqForceTM 10W (CAT TO-4)
- Clarity® Synthetic Hydraulic AW
- Rando® HDZ
- Ursa Hydraulic Oil 10W

Engine Crankcase

- Delo 600 ADF 15-40
- Delo 400 XSP 5W-40
- Delo 400 XLE SB 15W-40

Coolant System

Delo ELC Advanced Antifreeze/Coolant
Delo ELC Antifreeze/Coolant
Delo XLC Antifreeze/Coolant

Available as ISOCLEAN® Certified

These product recommendations provide general guidelines. All manufacturers have different coolant and lubricant requirements and recommendations. It will be important to contact a Chevron representative or refer to the Original Equipment Manufacturer manual to confirm the proper product is used for the application. Visit chevron-gsc.force.com/lubeteksupport for confirmation of specific OEM specifications.

Differentials & Gear Drives

- Delo TorqForce 50 (CAT TO-4)
- Delo TorqForce FD 60 (CAT FD-1)

Bearings and Grease Points

Rykon® HD
Rykon HD M5
Starplex® HD
Starplex HD M5
Starplex Syn EP M5
Starplex HD M3
Starplex EP M3

Transmissions

- Delo TorqForce Syn 5W-20 (CAT TO-4)
- Delo TorqForce MP (CAT TO-4M)
- Delo TorqForce 30 (CAT TO-4)



A Chevron company product

©2023 Chevron. All rights reserved. All trademarks are property of Chevron Intellectual Property LLC or their respective owners.